

The optimized balance between heat, vacuum, process design and an easy, user friendly operating system for removal of water and particulate from hydraulic and high viscosity lubricating oils. Equipped with generously sized, high efficiency filtration, the VUD is the ultimate oil purifier.

Keeping fluids clean and dry extends component and bearing life, increases productivity, minimizes downtime and extends useful fluid life. The VUD is ideal for removal of all forms of water, including free, emulsified and dissolved water and gas from hydraulic and lubricating oils.



hyprofiltration.com/VUD



#### Contamination is complicated. Removing it is easy.

With features including viscosity specific dispersal element designs, fin tube low watt density heaters, oversized particulate filter, adjustable recirculation line, auto phase detection and reversal, programmable thermostat, proprietary vacuum chamber level control, foam sensor and auto-drain, VUD is the ultimate contamination removal system.



#### Never stops working.

VUD is a workhorse designed for 24/7 unattended operation. With a dual condensate collection tank design, auto water level sensors and automatic drain valves, there is no need to stop to drain water. The oversized condenser and dual condensate collection tanks work together to keep the water out of the vacuum pump.





#### Results you can see.

Clear covers on the vacuum chamber and condensate collection tanks let you see what is really happening inside the VUD. You will know when you start removing water or when you are almost below saturation point with just a glance.



#### Integrated intelligence.

The VUD smart relay enabled control panel makes start-up and shut-down safe and operator friendly so that everything is controlled with the simple push of a button. To take it even further, the optional PLC Touch Screen provides operating controls and data right at your fingertips.

#### Filtration starts with the filter(s).

Particulate media options down to  $\beta 2.5_{\text{ICI}} = 1000$  and viscosity specific dispersal elements provide you with the best filtration and water removal capabilities in the world, period.





#### Completely, entirely, totally, all inclusive.

When it comes to comprehensive filtration and water removal, the buck stops here. VUD customization takes on many forms such as unique size requirements, combining VUD with other technologies such as FRF acid or turbine lube oil varnish removal, ATEX electrical standards, all to deliver the perfect oil purification system to meet your exact needs.

## The Unmatched Purification Process

#### How it works

Contaminated oil is drawn into the Vac-U-Dry purifier by a high output vacuum pump. The oil passes through the low watt density heater where heated to optimum temperature for the dehydration process (150°F, 66°C). The oil enters the vacuum chamber passing through specially designed dispersal elements which create a thin film of oil that is exposed to the vacuum. The water is vaporized and then drawn into the condenser where it liquefies and drains into the condensate tank.

The dehydrated oil flows to the bottom of the vacuum chamber and is removed by the discharge pump where it is pumped through the high efficiency particulate filter assembly  $(\beta x_{cl} > 1000)$  and returned to the system. The recirculating line helps the Vac-U-Dry reach optimum temperature in cold start situations and can be used to throttle machine inlet and outlet flow. From here, your oil can either be recirculated for additional temperature and contamination control or returned to your reservoir or equipment where it will operate more efficiently than ever.







### The Proven Performer



No other technology removes water faster or more safely with less chance of foaming than the Hy-Pro VUD. The graph here represents the estimated time required per model to remove water from 5000 ppm (0.5%) down to 150 ppm (0.015%) for increasing reservoir sizes.

### Vacuum Pump Options

VUDs come standard with several vacuum pump options to best suit your application needs. Options C and D offer maximum portability to use your VUD in almost any location. Whether you're using your VUD to service multiple systems or for service work, you'll have unmatched filtration everywhere you need it.



#### C – Dry Seal (Dry Rotary Claw)

Long maintenance interval (10,000 hour synchronizing gear oil change) and great for portability. With excellent corrosion resistance to condensate exposure, this offers our lowest cost of ownership vacuum pump option.



#### D – Dry Seal (Lubricated Rotary Vane)

500-750 hour maintenance interval (lubricating oil and filter change), excellent for portability, compact size and low weight. The D option vacuum pump offers our lowest initial cost of ownership.



#### L – Liquid Ring

Ideal for dedicated VUD applications where ambient conditions are hot and humid and portability is not required. Minimum 3 gpm (11 lpm) external process water is required. Maintenance includes maintaining clean process water and balancing compound pressure gauge.



#### Vacuum power that doesn't suck.

Pulled by the vacuum pump, oil passes through the heater housing and vacuum chamber dispersal elements, providing smooth flow for optimum water removal without foam. The tall vertical vacuum chamber achieves maximum oil film surface area on the dispersal elements, aided by proprietary variable flow level control, to remove water from your oil incredibly fast with unmatched consistency.





#### **Dispersal elements.**

Inside every VUD's vacuum chamber is the secret to its high efficiency water removal success. Viscosity range specific dispersal elements configured properly means faster water removal without the foaming issues that come with a one size fits all dispersal media for hydraulic and lube oils.

#### Take control of your system, automatically.

The Inlet Control Valve (N/C Solenoid) automatically closes when the VUD is not in operation, preventing the unit from siphoning fluid from a reservoir or flooding from a positive head inlet situation.





#### Synced to your system.

Achieve optimum VUD process temperature faster and ease start-up on high viscosity oils, especially when they're cold. Also ideal for adjusting overall VUD return flow down when using VUD on a small reservoir or gearbox. Simple and effective, the recirculation line adds incredible flexibility to fine tune the VUD to your system.

#### You can't beat the heat.

With no direct contact with the heating element, your turbine oil will safely and quickly get up to temperature without the risk of burning. The programmable temperature control with integral no-flow switch prevents oil damage and allows you to heat your fluids at your own pace. And what's more: all this comes standard on every VUD.



# **VUD** Specifications

Model	V3D	V5C	V5C V10C		V20C	V30C	V45C	V60C	V100C		
Height <sup>1</sup>	60" (152 cm)	75" (191 cm)	75" (191 cm)	75" (191 cm)	75" (191 cm)	89" (226 cm)	75" (191 cm)	89" (226 cm)	89" (226 cm)		
Length <sup>1</sup>	48" (122 cm)	56" (142 cm)	56" (142 cm)	56" (142 cm)	72" (183 cm)	84" (213 cm)	84" (213 cm)	96" (244 cm)	120" (305 cm)		
Width <sup>1</sup>	32" (82 cm)	32" (82 cm)	32" (82 cm)	32" (82 cm)	36" (91 cm)	40" (102 cm)	48" (122 cm)	60" (153 cm)	96" (244 cm)		
Weight <sup>1</sup>	850 lbs (386 kg)	2000 lbs (908 kg)	2400 lbs (1089 kg)	2500 lbs (1134 kg)	2800 lbs (1270 kg)	3100 lbs (1406 kg)	3400 lbs (1542 kg)	3700 lbs (1678 kg)	4600 lbs (2087 kg)		
Dispersal Element Quantity	2 x 11" (28 cm)	2 x 22" (56 cm)	3 x 22" (56 cm)	3 x 22" (56 cm)	4 x 22" (56 cm)	4 x 36" (91 cm)	8 x 22" (56 cm)	8 x 36" (91 cm)	16 x 36" (91 cm)		
Replacement Elements	Dispersa HP*EL11	I Elements HP*EL22	– use Dispe HP*EL22	ersal Eleme HP*EL22	nt code fro HP*EL22	m your equ HP*EL36	ipment pa HP*EL22	a <mark>rt number i</mark> HP*EL36	n place of *: HP*EL36		
	Filter Ele Filter Elen HP107L36 -	ments – us nent Part Nur - [Media Select	e correspor nber ion Code][Seal	t part num	nber:						
Operating Temperature	<b>Fluid Tem</b> 30°F to 180 (0°C to 82°	perature )°F C)			<b>Aml</b> -4°F (-20)	i <b>bient Temperature</b> F to 104°F IC to 40C)					
Materials of Construction	Frame Painted ste	eel & 304 stain	Filter a less Carbon	ssembly steel	<b>Con</b> Stair	<b>densate tank</b> nless steel	S	<b>Element bypass valve</b> Nylon			
Media Description	<b>M</b> G8 Dualgla of DFE rate media for a fluids. βx <sub>[C]</sub>	ss, our latest g d, high perfor all hydraulic & = 1000 (βx = 2	generation mance glass lubrication 200)	<b>A</b> G8 Dualgla media com scrim. βx <sub>[c]</sub>	s high performance Stainl bined with water removal media = 1000 (βx = 200)			steel wire mesh <sub>CI</sub> = 2 (βx = 2)	1		

<sup>1</sup>Dimensions are approximations taken from base model and will vary according to options chosen.



## **VUD Part Number Builder**

VUD											]_		_			
	Flow Rate		Vacuum Pump	Power Options	Dispersal Element	Media	Seals		Heaters	Condenser		Special Options	Ĩ	√ulti Function Jnit		
Flow Rate <sup>1</sup> 3 5 10 15 20			3 gpm (11 5 gpm (18 10 gpm (3 15 gpm (5 20 gpm (7	3 gpm (11 lpm) 5 gpm (18.9 lpm) 10 gpm (37.9 lpm) 15 gpm (56.8 lpm) 20 gpm (75.7 lpm)					<ul> <li>30 gpm (114 lpm)</li> <li>45 gpm (170 lpm)</li> <li>60 gpm (225 lpm)</li> <li>100 gpm (379 lpm)</li> </ul>							
Vacuum Pump Ty	ype C Dry seal (rotary claw) D Dry seal (lubricated rotary vane) L Liquid ring (external water supply required)															
Power Options		60 23 46 57	Hz 208-230 V 460-480 V 575 V ac, 1	/ ac, 3P / ac, 3P 3P				50   38 41 52	Hz 380 V ac, 3P 415 V ac, 3P 525 V ac, 3P							
Dispersa Element	al :	D P W	Pleated d Metallic p Pleated st	ispersal elem acked dispers tainless steel	ent - all synth sal element - dispersal eler	netic media (v not for use in ment (ISO VG	iscosity phosph 150-320	≤ ISO nate e ))	VG 220) ester systems	(viscosity ≥	SO	VG 460)				
Media Selectio	n	G8 1M 3M 6M 10N 16N 25N	$\begin{array}{c} \text{Dualglass} \\ \beta 2.5_{[C]} = 1 \\ \beta 5_{[C]} = 100 \\ \beta 7_{[C]} = 100 \\ \textbf{M}  \beta 12_{[C]} = 10 \\ \textbf{M}  \beta 17_{[C]} = 10 \\ \textbf{M}  \beta 22_{[C]} = 10 \\ \textbf{M}  \beta 22_{[C]} = 10 \end{array}$	000, β1 = 200 00, β3 = 200 00, β6 = 200 000, β12 = 200 000, β17 = 200 000, β25 = 200	) ) )			Stai 25W 40W 74W 149V	nless wire n 25μ nomina 40μ nomina 74μ nomina <b>V</b> 149μ nomin	nesh al al al nal						
Seals		V E <sup>2</sup>	Fluorocar EPR seals	່bon (for Skydrol ເ	ise)											
Heaters		9 12 24 36	9 kW 12 kW 24 kW (2 x 36 kW (3 x	x 12 kW) x 12 kW)				48 64 80 96	48 kW (4 x 1) 64 kW (4 x 1) 80 kW (5 x 1) 96 kW (6 x 1)	2 kW) 5 kW) 5 kW) 5 kW)						
Conden	ser	A B L	Air coolec Air & liqui Liquid coo	d id cooled pled												
Special Options		8 B C D E F G H J K L M O	8" solid w Auto cond Pre-filter CE marke Dirty filter Carbon va Vacuum o 316 stainle Manual re Individual Sight flow Lifting eye Discharge On-board	heel upgrade densate drain bag filter hou d + internatio r indicator ala acuum pump chamber foan ess condensate set hour mete heater selecto indicator (whe e kit e line flow me I PM-1 particle	sing nal crating (V rm light exhaust filter ing sensor e wet parts (30- er (in addition or switches eel type) ter e monitor	/5-V60) r 4 standard) to std. non-res	set)	P Q <sup>4,5</sup> P9 <sup>6</sup> R <sup>3</sup> S S9 <sup>7</sup> T <sup>4</sup> U V <sup>4</sup> W X <sup>8</sup> Y Z	PLC touch so Maintenanco Phosphate e Electrical ph Inlet line bas Skydrol fluid Hose kit (suc 50' (15 m) ele Inlet control Water senso Explosion pr VFD variable On site start	reen operat e spares & re ster fluid con ase reversal sket strainer compatibilit tion & return ectrical cord valve (for po r and indicat oof - Class 1, speed moto -up training	ion epa mp sw sy n h wit osit tor , Di or fi (1 >	e & data ir kit atibility moc itch nodification oses + wand thout plug ive head inle iv 2 Group C- requency co < 10 hour shi	ific s) +D ntro ft)	ation		
Multi Fu Units	nction	om COT ICB SVR	it Sta r CC PE <sup>9</sup> Ph t1200CT <sup>9</sup> Va	andard VUD c OT coalesce ve losphate este rnish remova	apabilities essel adder + r acid & disso l & preventio	auto water d blved metal re n side loop (5	rain fun moval ( gpm co	ction conta ntinu	(sized to han let factory for lous element	dle 100% of alternate flu flow up to 80	VUI iids	D flow) 5) ) gal/30,000 l	iter	r reservoir)		

<sup>1</sup>Nominal flow rates at 60 Hz motor speeds.

<sup>2</sup>Contact factory for other fluid option compatibility.

<sup>3</sup>Standard supplied options, must be included in part number. <sup>4</sup>Recommended option.

\*Repair & spares kit includes common consumable and select critical spares such as flow switches, fuses, and tank lids.
 \*When selected, must be paired with Seal option "V." Contact factory for more information or assistance in fluid compatibility.
 \*When selected, must be paired with Seal option "E." Contact factory for more information or assistance in fluid compatibility.
 \*Consult factory for other explosion proof options.

Narnish and IĆB add-on technologies condition a portion of maximum VUD flow. Standard SVR1200CT flow rate ≤ 5 gpm. ICB add-on will be sized to reservoir volume.

